

CLAIMS

1. Apparatus for spraying fluid onto an object in a treatment location having a floor and comprising:

- a support structure overhead the location
- a spray nozzle carrier arm of essentially inverted L-shape having a horizontal spray portion extending from an inboard end generally over the center line of the location to a second end at the periphery of the location; said arm further having a vertical spray portion essentially continuous with the horizontal portion and extending from the second end thereof downwardly toward the floor;
- spray nozzles carried by said arm;
- a powered pivot structure connecting said arm to said support structure to pivot said arm about a vertical axis passing substantially through the inboard end of the first portion whereby the vertical portion of the arm may be caused to circumscribe at least a portion of the area ; and
- means for supplying fluid to the nozzles under pressure.

2. Apparatus as defined in claim 1 wherein said support structure defines a longitudinal path of travel and said apparatus further comprises:

- a carriage structure mounted for longitudinal movement over and relative to the treatment location;
- a reversible carriage drive system; and

23

7 said powered pivot structure being mounted on said carriage.

1 3. Apparatus as defined in claim ~~3~~¹ further including a shuttle
2 structure mounted on said carriage and including a shuttle drive system for
3 selectively causing movement of said shuttle and pivot structure laterally of said
4 support structure and carriage.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

4 Apparatus as defined in claim 3 further comprising a
programmable controller having outputs connected to the pivot structure, said
carriage drive and said shuttle drive.

5 5. Apparatus as defined in claim 4 wherein said programmable
6 controller includes means for programmably controlling the speed of movement
7 of said carriage and shuttle drives.

1 6. Apparatus as defined in claim 5 wherein said programmable
2 controller comprises a variable frequency generator.

1 7. Apparatus as defined in claim 5 wherein said programmable
2 controller comprises a key pad input.

24

1 8. Apparatus as defined in claim 1 further including a
2 resettable, breakaway joint disposed between and interconnecting said first and
3 second carrier arm portions for permitting nondestructive relative movement
4 between said portions when said second arm is subjected to a force.

1 9. Apparatus as defined in claim 1 wherein said means for
2 supplying said nozzles with fluid comprises a fluid source and has multiple
 pressure settings.

1 10. Apparatus as defined in claim 1 wherein said support
2 structure comprises a pair of spaced, parallel hollow beams suspended over the
3 washing area, at least one cross beam extending between and supported by
4 said pair of beams;

5 said apparatus further comprising a carriage mounted for powered,
6 reversible travel on said beams, a shuttle structure mounted for powered,
7 reversible movement on said carriage cross beam and laterally of said pair of
8 beams.

1 11. Apparatus as defined in claim 10 further comprising means
2 for adjusting the lateral spacing between said pair of parallel beams.

25

1 12. Apparatus as defined in claim 10 further comprising means
2 for supplying heated liquid to the interior spaces of the beams.

1 13. A pressure washer for an object in a washing area
2 comprising:
3 a support structure over said area;
4 a pair of spray nozzle carrier arms each being of essentially
5 inverted L-shaped configuration and having a first portion extending from a
6 center point toward the periphery of the area and a second contiguous vertical
7 portion disposed adjacent to the area;
8 spray nozzles carried by each of said carrier arms;
9 a pivot structure connecting said carrier arms to said support
10 structure at said center point to reversely pivot said carrier arms whereby the
11 vertical portions of said carrier arms may be caused to follow reversely similar,
12 essentially mirror image paths which together circumscribe the area; and
13 means for supplying fluid to the nozzles under pressure.

1 14. Apparatus as defined in claim 13 wherein said support
2 structure defines the longitudinal path of travel;
3 said apparatus further comprising a carriage structure mounted for
4 longitudinal movement over and relative to the washing area, said pivot structure
5 be mounted on said carriage for movement therewith.

26

1 15. Apparatus as defined in claim 14 further including a shuttle
2 structure mounted on said carriage structure for bidirectional lateral movement
3 relative to said arms.

1 16. Apparatus as defined in claim 13 further including a
2 resettable breakaway joint disposed between interconnecting each of said first
3 and second carrier portions for permitting nondestructive controlled relative
4 movement between said portions.

1 17. Apparatus as defined in claim 13 further comprising a
2 programmable controller for controlling the movement of said support structure
3 relative to said washing area.

1 18. Apparatus as defined in claim 17 wherein said
2 programmable controller comprises means for controlling the speed of
3 movement of said carriage.

1 19. Apparatus as defined in claim 18 wherein said
2 programmable controller comprises a display.

29

1 20. Apparatus as defined in claim 19 wherein said
2 programmable controller comprises a key pad.

1 21. Apparatus as defined in claim 1 wherein said means for
2 supplying said nozzles with washing fluid comprises at least two fluid sources.

1 22. A pressure washer for an object in a washing area
2 comprising:
3 a support structure over said area;
4 a pair of spray nozzle carrier arms each being of essentially
5 inverted L-shaped configuration and having a first portion extending from a
6 center point toward the periphery of the area and a second contiguous vertical
7 portion disposed adjacent to the area;
8 spray nozzles carried by each of said carrier arms;
9 a pivot structure connecting said carrier arms to said support
10 structure at said center point to reversely pivot said carrier arms whereby the
11 vertical portions of said carrier arms may be caused to follow reversely similar,
12 essentially mirror image paths which together circumscribe the area; and
13 means for supplying fluid to the nozzles under pressure wherein
14 said means for supplying said nozzles with washing fluid comprises at least two
15 fluid sources.

Suba3

1 23. Apparatus as defined in claim 22 wherein said support
2 structure comprises a pair of spaced parallel beams dispersed over the washing
3 area, at least one cross beam extending between and supported by said pair of
4 longitudinal beams, and a shuttle structure mounted on the support for powered
5 programmably coordinated movement along said beams.

1 24. Apparatus as defined in claim 22 further including means
2 for determining the location of a vehicle in said area.

1 25. A method of pressure washing a vehicle which is disposed
2 in a washing area comprising the steps of:

3 providing a spray nozzle carrier arm of essentially inverted L-shape
4 having a first horizontal portion which is disposed over the area and a
5 contiguous, second vertical portion which is disposed adjacent the periphery of
6 the area;

7 causing said carrier arm to circumscribe at least part of the area
8 and to pivot about an end of the arm which is generally over the center of the
9 area; and

10 supplying washing fluid to the nozzles under pressure.

29

1 26. A method as defined in claim 25 wherein the step of
2 circumscribing is carried out so as to maintain a substantially constant spacing
3 between the vertical arm portion and a vehicle in the area.

1 27. A method of washing a vehicle having top, front, rear and
2 side surfaces while standing in a washing area comprising the steps of:
3 providing a pair of spray nozzle carriers each of essentially
4 inverted L-shape and each having first horizontal portions which overlie the
5 washing area and second vertical portions which are adjacent the washing area;
6 causing said carriers to pivot from the inboard distal ends of said
7 horizontal portions in a reversely similar fashion so as to fully circumscribe said
8 area and said vehicle while maintaining a substantially constant spacing from
9 the side surfaces of said vehicle; and
10 supplying said nozzle carriers with washing fluid under pressure.

1 28. A method of washing a vehicle in a washing area
2 comprising the steps of:
3 providing a pair of reversibly similar spray nozzle carriers of
4 inverted L-shape having a substantially common pivot center over the area;
5 moving the carriers through a butterfly pattern while moving the
6 pivot center along and over the centerline of the vehicle while simultaneously
7 supplying both carriers with fluid; and

30

8 moving each carrier sequentially through a butterfly pattern at a
9 predetermined optimal distance from the vehicle while supplying each carrier
10 independently with fluid.

0944221 100130

31